

# INSTALLATION GUIDE

Individual solid wood blade for walls, ceilings & furniture

**IMPORTANT :** It is recommended that the product be stored flat in an area where the ambient temperature is between 65°F and 86°F (10°C and 30°C) and the relative humidity between 25% RH and 55% RH. For the installation of the product, it is recommended to use the following tools (not included): construction adhesive cartridge, a table saw and/or a miter saw and/or a circular saw, a level, a pneumatic nail gun, finishing nails (18 or 23 gauge). Upon receipt of the product, and especially before its installation, please check that the product conforms to the order and notify WoodzCo within seven (7) days of receipt of any defect/damage to the product. For details, refer to the WoodzCo [Limited Warranty](#) on our website [www.woodzco.com](http://www.woodzco.com). It is recommended that the installation work be entrusted to a worker with the necessary skills to ensure proper installation that complies with the recommendations.

**PLEASE read all instructions of the installation guide before starting your work. This installation requires a detailed installation plan, careful planning and precise measurements.**

NOTE : For indoor use only. A rigid surface (eg. plywood, MDF, particles, etc.) is necessary on the entire surface to be covered to ensure the stability of the product. Beforehand, make sure that the wall, ceiling or furniture has been properly prepared and/or paint to receive SOLO solid wood blades.

## 1. Installation plan

Before starting the installation of the wood blades, it is important to establish your installation plan. Determine the orientation of the blades and measure the dimensions of the surface to be covered to calculate the positioning and the distance between the blades.

## 2. Fixing

Apply construction adhesive to the back of the wood blade. Place the wood blade on the surface to be covered in the right location and level according to your installation plan. Holding it in place, insert several finishing nails (18 or 23 gauge).

## 3. Conclusion

Continue installing the wood blades in order to cover the entire surface of your project.

## CUTTING PROCEDURE

NOTE: In accordance with the manufacturer's recommendations, it is possible to cut a panel so that it is custom-made for your project.

1. With a pencil, make a cut line at the desired location on the wood blade.
2. Using a saw, cut the wood blade along the cut line. Proceed carefully to ensure a clean cut without damaging the wood blade.
3. Be sure to seal the ends of freshly cut wood blades with the touch-up kit provided with the wood blades. Be sure to seal only the ends and not the faces of the wood blades as this may alter the luster or color.

For **cleaning and maintenance** recommendations, refer to the CARE GUIDE on our website [www.woodzco.com](http://www.woodzco.com).